SAFTIFIRST™ FIRE RATED GLAZING SOLUTIONS Since 1982

Quick Quote

Quotation Request Form

IN AN EFFORT TO PROVIDE YOU WITH AN ACCURATE AND TIMELY QUOTE, PLEASE COMPLETE THE FORM BELOW:

Company Name: _____ Date: _____

Contact Person: _____ Project Name: _____

Address: _____

City: _____ State: _____ Zip: _____ Architect: _____

Phone: _____ Fax: _____ City/State: _____

Email: _____ Date Product Required: _____

Fire Rated Glazing: (Please attach any additional information)

SuperLite I
Clear specialty tempered.
CPSC Cat. II impact safety rated.
☐ 20 min ☐ 30 min ☐ Use Starphire by PPG

SuperLite I-W
Safety wired glass. CPSC Cat. II impact safety rated.
___ Misco (Diamond)
___ Baroque (Square)
☐ 20 min ☐ 45 min ☐ 60 min ☐ 90 min

SuperLite I-XL
Directional heat reflective specialty tempered.
CPSC Cat. II impact safety rated.
☐ 20 min ☐ 45 min ☐ 60 min

SuperLite I-XL IGU
Bi-directional, heat reflective specialty tempered.
CPSC Cat. II impact safety rated.
☐ 20 min ☐ 45 min ☐ 60 min

Pyran® Platinum
Premium non-safety ceramics.
☐ 20 min ☐ 45 min ☐ 60 min ☐ 90 min

Pyran® Platinum F
Premium filmed safety ceramics.
CPSC Cat. II impact safety rated.
☐ 20 min ☐ 45 min ☐ 60 min ☐ 90 min ☐ 180 min

Pyran® Platinum L
Premium safety ceramics.
CPSC Cat. II impact safety rated.
☐ 20 min ☐ 45 min ☐ 60 min ☐ 90 min ☐ 180 min

SuperLite II-XL
Fire resistive transparent wall glazing.
Meets ASTM E-119.
CPSC Cat. II impact safety rated.
☐ 45 min ☐ 60 min ☐ 90 min ☐ 120 min ☐ Use Starphire by PPG

Int./Ext.	Qty.	Width	Height	Additional Comments

Fire Rated Framing: PLEASE FAX OR EMAIL SPECIFICATIONS AND DRAWINGS:

- **SAFTI*fire* GPX** – 45 to 120 minute fire resistive, temperature rise framing system. Meets ASTM E-119.
- **SAFTI*fire* HM** – 20 to 45 minute fire protective, non-temperature rise hollow metal framing system.
- **SAFTI*fire* HMTR** – 60 to 90 minute temperature rise hollow metal framing system.
- **SAFTI*fire* CW** – 45 to 120 minute temperature rise framing system for multi-story spans of glass. Meets ASTM E-119.

PLEASE FAX THIS COMPLETED FORM TO 415.824.5900. THANK YOU!

For questions, please call 888.653.3333 or visit www.safti.com.